



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
05



EN 14411

Piastrelle di ceramica pressate a secco per rivestimenti interni

Indoor wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour revêtements internes

Trockengepresste Wandfliesen für innen Bereiche

Azulejos de cerámica prensados en seco para revestimientos para interiores

SERIE: BIII GL	VALORI DICHIARATI Declared values Valeurs déclarées Realistische Werte / Valores declarados				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd Cd-Freisetzung Cesión de Pb y Cd

ALABASTRO				
ALO'				
ALTEMPTS				
APTA				
ARCHEO				
ARCIPELAGO				
ARMONY				
ARTE MUSIVA				
ART-FIBER				
ATMOSFERE				
CASALI				
CICLADI				
DHUSHARA				
DOMUS				
ESSENZE				
FORME				
GIARDINO				
GRANITI				
I NATURALI				
LE PORCELLANE				
MARMI NATURALI				
MEDITERRANEO				
MODERN	A1	s*>7,5mm F>600 N	s*>7,5mm σ >15 N/mm ²	NPD*
MOON				
OASI				
OPERE				
ORGANZA				
PASTELLI				
PERLE				
PIETRE ANTICHE				
PIETRE NATURALI				
PROFUMI				
SAMARKANDA				
SANDSTONE				
SPEZIE				
STICK				
TERRAMARE				
TEXTIL				
TRAVERTINO				
TREND				
TROPICAL				
VETUS				
VILLAGE				
WALD				
WALL ART				
WEB & LOG				
WHITE				
X-OTIC				
X-PERIENCE				

*Spessore: Thickness
Epaisseur
Stärke
Espesor

*NPD: No performance declared
Aucune performance déclarée
Keine Leistungsangabe
Ninguna prestación declarada

	FINCIBEC SPA VIA VALLE D'AOSTA 47 41049 SASSUOLO (MO) 05	
EN 14411 Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni <small>Indoor and outdoor floor and wall dry-pressed ceramic tiles</small> <small>Carreaux céramiques pressés à sec pour sols et revêtements internes et externes</small> <small>Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich</small> <small>Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores</small>		

NOME SERIE: BI b GL	VALORI DICHIARATI <small>Declared values</small> <small>Valeurs déclarées</small> <small>Realistische Werte / Valores declarados</small>							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	<small>Fire reaction</small> <small>Réaction au feu</small> <small>Feuerreaktion</small> <small>Reacción al fuego</small>	<small>Breaking load</small> <small>Charge de rupture</small> <small>Bruchkraft</small> <small>Carga de rotura</small>	<small>Flexion resistance</small> <small>Résistance à la flexion</small> <small>Biegefestigkeit</small> <small>Resistencia a la flexión</small>	<small>Adhesion resistance</small> <small>Résistance d'adhésion</small> <small>Haftwiderstand</small> <small>Resistencia a la adhesión</small>	<small>Slipperiness</small> <small>Glissement</small> <small>Rutschfestigkeit</small> <small>Deslizamiento</small>	<small>Friction resistance</small> <small>Résistance au frottement</small> <small>Reibungswiderstand</small> <small>Resistencia a la fricción</small>	<small>Frost / thaw resistance</small> <small>Durabilité Gel / Dégel</small> <small>Frost / Tau-Beständigkeit</small> <small>Durabilidad Heladas / Deshielo</small>	<small>Pb Cd release</small> <small>Cession Pb Cd</small> <small>Pb - Cd-Freisetzung</small> <small>Cesión de Pb y Cd</small>
	A1 _{fl} A1	F>1300 N	σ>35 N/mm ²	NPD*	NPD*	Resiste Resistant Résiste Beständig Resistente	NPD*	

ALTEPTS							
APTA							
ARCIPELAGO							
ART-FIBER							
ATMOSFERE							
AUREA							
CICLADI							
DHUSHARA							
ESSENZE							
FORME							
CANYONLAND							
GRANITI							
I NATURALI							
LATINA							
LE PORCELLANE							
LEBEN							
MARMI NATURALI							
MIRA							
MOON							
PIETRA SACRA							
PIETRE ANTICHE							
PIETRE NATURALI							
SANDSTONE							
STICK							
TERRAMARE							
TREND							
UNIVERSAL							
VETUS							
WALL ART							

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
06



EN 14411

Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni

Indoor and outdoor floor and wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour sols et revêtements internes et externes

Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich

Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores

NOME SERIE: BI b GL	VALORI DICHIARATI Declared values Valeurs déclarées Realistische Werte / Valores declarados							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Slipperiness Glissement Rutschfestigkeit Deslizamiento	Friction resistance Résistance au frottement Reibungswiderstand Resistencia a la fricción	Frost / thaw resistance Durabilité Gel / Dégel Frost / Tau-Beständigkeit Durabilidad Heladas / Deshielo	Pb Cd release Cession Pb Cd Pb - Cd-Freisetzung Cesión de Pb y Cd
Maxima	A1 - A1fl	F>1300 N	$\sigma > 5$ N/mm ²	NPD*			Resiste Resistant Résiste Beständig Resistente	NPD*
Sari								
Sunset								

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
07



EN 14411

Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni

Indoor and outdoor floor and wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour sols et revêtements internes et externes

Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich

Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores

NOME SERIE: B1a GL	VALORI DICHIARATI Declared values Valeurs déclarées Realistische Werte / Valores declarados							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Slipperiness Glissement Rutschfestigkeit Deslizamiento	Friction resistance Résistance au frottement Reibungswiderstand Resistencia a la fricción	Frost / thaw resistance Durabilité Gel / Dégel Frost / Tau-Beständigkeit Durabilidad Heladas / Deshielo	Pb Cd release Cession Pb Cd Pb - Cd-Freisetzung Cesión de Pb y Cd
Matrix	A1 - A1fl	F>1300 N	$\sigma > 5 \text{ N/mm}^2$	NPD*			Resiste Resistant Résiste Beständig Resistente	NPD*
Zillij								
Chinè								
Ghibli								
Opus								

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
08



EN 14411

Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni

Indoor and outdoor floor and wall dry-pressed ceramic tiles
Carreaux céramiques pressés à sec pour sols et revêtements internes et externes
Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich
Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores

NOME SERIE: B1a GL	VALORI DICHIARATI Declared values Valeurs déclarées Realistische Werte / Valores declarados							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Slipperiness Glissement Rutschfestigkeit Deslizamiento	Friction resistance Résistance au frottement Reibungswiderstand Resistencia a la fricción	Frost / thaw resistance Durabilité Gel / Dégel Frost / Tau-Beständigkeit Durabilidad Heladas / Deshielo	Pb Cd release Cession Pb Cd Pb - Cd-Freisetzung Cesión de Pb y Cd
Kilim Marble Hill Vanity Satin Onstage Perlage Materia	A1 - A1fl	F>1300 N	$\sigma > 5 \text{ N/mm}^2$		NPD*		Resiste Resistant Résiste Beständig Resistente	NPD*

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
09



EN 14411

Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni

Indoor and outdoor floor and wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour sols et revêtements internes et externes

Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich

Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores

NOME SERIE: BIa GL	VALORI DICHIARATI							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Slipperiness Glissement Rutschfestigkeit Deslizamiento	Friction resistance Résistance au frottement Reibungswiderstand Resistencia a la fricción	Frost / thaw resistance Durabilité Gel / Dégel Frost / Tau-Beständigkeit Durabilidad Heladas / Deshielo	Pb Cd release Cession Pb Cd Pb - Cd-Freisetzung Cesión de Pb y Cd
Beverly	A1 - A1fl	F>1300 N	$\sigma > 5$ N/mm ²	NPD*			Resiste Resistant	NPD*
Greenway	A1 - A1fl	F> 700 N	$\sigma > 5$ N/mm ²	NPD*			Resiste Resistant	NPD*
Fire - 5 mm -	A1 - A1fl	F> 700 N	$\sigma > 5$ N/mm ²	NPD*			Resiste Resistant	NPD*

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
10



EN 14411

Piastrelle di ceramica pressate a secco per pavimentazione e rivestimenti interni ed esterni

Indoor and outdoor floor and wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour sols et revêtements internes et externes

Trockengepresste Keramik-Boden- und Wandfliesen für den Innen- und Außenbereich

Azulejos de cerámica prensados en seco para pavimentos y revestimientos para interiores y exteriores

NOME SERIE: B1a GL	VALORI DICHIARATI							
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Scivolosità	Resistenza all'attrito	Durabilità Gelo/disgelo	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Slipperiness Glissement Rutschfestigkeit Deslizamiento	Friction resistance Résistance au frottement Reibungswiderstand Resistencia a la fricción	Frost / thaw resistance Durabilité Gel / Dégel Frost / Tau-Beständigkeit Durabilidad Heladas / Deshielo	Pb Cd release Cession Pb Cd Pb - Cd-Freisetzung Cesión de Pb y Cd
Desert	A1 - A1fl	F>1300 N	$\sigma > 5 \text{ N/mm}^2$	NPD*			Resiste Resistant	NPD*

*NPD: No performance declared / Aucune performance déclarée / Keine Leistungsangabe / Ninguna prestación declarada

	FINCIBEC SPA VIA VALLE D'AOSTA 47 41049 SASSUOLO (MO) 06	
EN 14411 Piastrelle di ceramica pressate a secco per rivestimenti interni		
Indoor wall dry-pressed ceramic tiles Carreaux céramiques pressés à sec pour revêtements internes Trockengepresste Wandfliesen für innen Bereiche Azulejos de cerámica prensados en seco para revestimientos para interiores		

SERIE: BIII GL	VALORI DICHIARATI Declared values Valeurs déclarées Realistische Werte / Valores declarados				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd Pb - Cd Freisetzung Cesión de Pb y Cd

Tricot	A1	s*>7,5mm	s*>7,5mm	NPD*
Sunset		F>600 N	σ >15 N/mm2	
Sari		s*<7,5mm	s*<7,5mm	
		F>200 N	σ >12 N/mm2	

*Spessore: Thickness
 Epaisseur
 Stärke
 Espesor

*NPD: No performance declared
 Aucune performance déclarée
 Keine Leistungsangabe
 Ninguna prestación declarada

	FINCIBEC SPA VIA VALLE D'AOSTA 47 41049 SASSUOLO (MO) 07	
EN 14411 Piastrelle di ceramica pressate a secco per rivestimenti interni Indoor wall dry-pressed ceramic tiles Carreaux céramiques pressés à sec pour revêtements internes Trockengepresste Wandfliesen für innen Bereiche Azulejos de cerámica prensados en seco para revestimientos para interiores		

SERIE: BIII GL	VALORI DICHIARATI Declared values Valeurs déclarées/Realistische Werte / Valores declarados				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd - Cd- Freisetzung Cesión de Pb y Cd

Zillij	A1	s*>7,5mm	s*>7,5mm	NPD*
X-cite				
Bloom		F>600 N	σ>15 N/mm2	
Silk				
Chiné		s*<7,5mm	s*<7,5mm	
Ghibli				
Work		F>200 N	σ>12 N/mm2	

*Spessore: Thickness Epaisseur Stärke Espesor

*NPD: No performance declared Aucune performance déclarée
Keine Leistungsangabe Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
09



EN 14411

Piastrelle di ceramica pressate a secco per rivestimenti interni

Indoor wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour revêtements internes

Trockengepresste Wandfliesen für innen Bereiche

Azulejos de cerámica prensados en seco para revestimientos para interiores

SERIE: BIII GL	VALORI DICHIARATI				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd Pb - Cd - Freisetzung Cesión de Pb y Cd

Beverly	A1	F>600 N	$\sigma > 15$ N/mm ²	NPD*
Stratos				
Greenway				
Tiffany				

*Spessore: Thickness
Epaisseur Stärke Espesor

*NPD: No performance declared
Aucune performance déclarée



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
08



EN 14411

Piastrelle di ceramica pressate a secco per rivestimenti interni

Indoor wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour revêtements internes

Trockengepresste Wandfliesen für innen Bereiche

Azulejos de cerámica prensados en seco para revestimientos para interiores

SERIE: BIII GL	VALORI DICHIARATI Declared values Valeurs déclarées/Realistische Werte / Valores declarados				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd Pb - Cd - Freisetzung Cesión de Pb y Cd

Kilim	A1	F>600 N	$\sigma > 15 \text{ N/mm}^2$	NPD*
Fun				
Marble Hill				
Vanity				
Satin				
Onstage				
Perlage				
Materia				

*Spessore: Thickness
Epaisseur Stärke Espesor

*NPD: No performance declared
Aucune performance déclarée
Keine Leistungsangabe
Ninguna prestación declarada



FINCIBEC SPA
VIA VALLE D'AOSTA 47
41049 SASSUOLO (MO)
10



EN 14411

Piastrelle di ceramica pressate a secco per rivestimenti interni

Indoor wall dry-pressed ceramic tiles

Carreaux céramiques pressés à sec pour revêtements internes

Trockengepresste Wandfliesen für innen Bereiche

Azulejos de cerámica prensados en seco para revestimientos para interiores

SERIE: BIII GL	VALORI DICHIARATI				
	Reazione al fuoco	Forza di rottura	Resistenza a flessione	Resistenza all'adesione	Cessione Pb Cd
	Fire reaction Réaction au feu Feuerreaktion Reacción al fuego	Breaking load Charge de rupture Bruchkraft Carga de rotura	Flexion resistance Résistance à la flexion Biegefestigkeit Resistencia a la flexión	Adhesion resistance Résistance d'adhésion Haftwiderstand Resistencia a la adhesión	Pb Cd release Cession Pb Cd Pb - Cd- Freisetzung Cesión de Pb y Cd

Laser	A1	F>600 N	$\sigma > 15$ N/mm ²	NPD*
Desert				

*Spessore: Thickness
Epaisseur Stärke Espesor

*NPD: No performance declared
Aucune performance déclarée